



BenQ MP-626 Projector

SPECIFICATIONS

TOP



FRONT



BACK



Native Resolution XGA (1024 x 768)

Projection System DLPTM technology by Texas Instruments®

Brightness 2700 ANSI lumens

Lamp 180W, 3500/4000 hours (Normal/Economic mode)

Contrast Ratio 3000:1 (Full on/Full off)

Weight 2.75kg

Noise Level 30/28 dB (Normal/Economic mode)

Resolution Support VGA(640 x 480) to UXGA(1600 x 1200)

Dimensions 12 x 3.8 x 8.5 inch (306 x 97 x 216 mm)

Image Size 23" to 300"

Throw Ratio 1.93-2.16 (51"@2M)

Zoom Ratio 1.1:1

Lens F : 2.52 (Wide) ~ 2.73 (Tele), f : 21.8mm (Wide) ~ 24mm (Tele)

Horizontal Frequency 31-90 kHz

Vertical Scan Rate 50-85 Hz

Input Terminals PC : Analog RGB: D-sub 15 pin x 1 Component Video: D-sub 15 pin (Shared with Analog RGB connector) S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 Audio : Stereo mini jack x 1P

Output Terminals PC D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1 10W x 1

Video Compatibility NTSC, PAL, SECAM

Power Consumption 230W, Standby < 1W

On-Screen Display Language English, French, German, Italian, Spanish, Russian, Traditional Chinese, Simplified Chinese, Japanese, Korean, Swedish, Dutch, Turkish, Czech, Portuguese, Thai, Polish

Functions Brilliant Color Standby D-Sub Output Auto Source (Auto Search) Resolution Reminder 11 Sets of Picture Mode Power Saving (Auto off) Wal Color Correction Blank Security Password High Altitude Mode Freeze Lamp Care

Accessories (Standard) Quick start guide, Manual, CD, Remote Control w/battery, Soft carry case, VGA cable, Power cord, RS232 Cable, Presentation plus, Spare lamp kit

2901 Technology Dr., Ste 135 • Plano, TX 75074
 toll-free: 800-399-1903 • phone: 972-881-3318
 fax: 972-881-0985
 visit us at: www.newline-whiteboards.com
 e-mail: info@newlineproductinc.com

Newline