





Newline Products, Inc  
2901 Technology Dr, Suite 135  
Plano, Texas 75074  
Tel: (972)-881-3318  
Fax: (972)-881-0985

CLASSIC COLLECTION


TECHNICAL DATA PACKAGE




ONE TIER




DOUBLE TIER




TRIPLE TIER




FOUR TIER




FIVE TIER




SIX TIER



2 PERSON



16 PERSON



WALL MOUNT



Newline Products, Inc  
2901 Technology Dr, Suite 135  
Plano, Texas 75074  
Tel: (972)-881-3318  
Fax: (972)-881-0985

CLASSIC COLLECTION

Locker Specification

## SPECIFICATION

**Material** - All major steel parts shall be of mild cold rolled commercial quality steel.

**Finish** - All material shall be powder washed and phosphate treated for maximum finish color adhesion. All components shall be finished with a hybrid epoxy/polyester powder, electrostatically applied to ensure uniform thickness and baked to cure.

**Construction** - All lockers shall be built on a unit principle with common intermediate uprights separating units.

**Door Frames** - Shall be 16 gauge formed in a channel shape. Vertical members shall have additional flange to provide a continuous door strike. Cross frame members shall also be 16 gauge channel shaped.

**Doors** - Shall be 16 gauge with louvers for ventilation, channel shaped on both the lock and hinge side, with angle formations across the top and bottom.

**Body** - Bottoms, tops, sides, backs and shelves shall be 24 gauge. Bolt spacing shall not exceed 9" o.c.

**Hinges** - Shall be full length 16 gauge continuous piano type riveted to both door and frame.

**Handles** - Shall be one-piece 21 gauge deep drawn stainless steel cup designed to accommodate locks.

**Latching** - The latching trigger shall be 14 gauge steel, attached to the latching channel. The trigger shall have a padlock eye for use with 9/32" diameter padlock shackle. Door to have latch clip engaging frame at three points on doors over 42" high and two points on all other doors. Locking devices to be positive automatic type, whereby locker door may be locked when open, then closed without unlocking. A rubber silencer shall be firmly secured to the frame at each latch hook.

**Interior Equipment** - Lockers 48" or higher shall be equipped with a shelf. If under 18" deep, locker shall have three wall hooks and one ceiling hook. Lockers 15" and 18" wide shall have four wall hooks and one ceiling hook.

**Number Plates** - Each locker shall have a polished aluminum number plate riveted to door face with black numerals 1/2" high.

**Color** - Doors and exposed body parts shall be selected from standard designer color ranges. Non-exposed body parts shall be finished in #03 Almond.

**Assembly** - All locker components shall be assembled with rivets.

**Optional** - Welded locker is also available, all body parts are welded into a single unit and shipped pre-assembled. (The difference from KD locker: 14 gauge door, the body: backs shall be 18 gauge; all other body parts shall be 16 gauge). Groupings will be determined by NPI based on the floor plan layout drawings submitted with the order.

**Installation** - Lockers shall be installed in accordance with installation instructions and shall be level and plumb with flush surfaces and rigid attachment to anchoring surfaces.