



Hitachi CP-A52 Projector

SPECIFICATIONS

TOP



FRONT



RIGHT SIDE



Specifications

Liquid Crystal Panel Structure	0.63" Polysilicon Active-matrix TFT x 3
Number of Pixels	786,432 Pixels
Resolution	Video: 540 TV lines / RGB: 1024 dots x 768 lines
Colors	16.7 million colors
Aspect Ratio	Native 4:3 / 16:9 compatible
Lens	Fixed
Throw Ratio (distance : width)	0.37
Lamp	220W UHB
Brightness	2,000 lumens
Expected Lamp Life	Approximately 2,000 hours (bright) or 3,000 hours (normal)
Contrast Ratio	500:01:00
Speaker Output	7W (1 speaker)
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	340W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB: VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16" Composite Video: NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N Component Video: 480i, 576i, 480p, 720p, 1080i
Acoustic Noise Level	33 dB (28 dB in whisper mode)
H-Sync	15 kHz - 106 kHz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 5°
Approvals	UL, C-UK, FCC, CE, RoHs
RGB Input	Analog RGB: 15-pin D-sub connector x2 Output RGB: 15-pin D-sub connector x 1
Video Input	S-Video: Mini DIN 4-pin connector x 1 Composite Video: RCA jack x 1 Component Video: RCA jack x 3
Audio	Input: Stereo mini jack x 2, RCA (I/R) x 1 pair Output: Stereo mini jack x 1
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Dimensions (W x D x H)	397 x 356 x 131 mm
Weight	5.8 kg
Additional Features	Kensington Slot, MyMemory / MyScreen / MyButtons, Digital Gamma Correction, Whiteboard/Blackboard Mode, Input Source Naming
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label
Lamp	DT00893
Remote Control	HL02488
Filter	UX35381

2901 Technology Dr., Ste 135 • Plano, TX 75074
 toll-free: 800-399-1903 • phone: 972-881-3318
 fax: 972-881-0985
 visit us at: www.newline-whiteboards.com
 e-mail: info@newlineproductinc.com

Newline